

## AMGBacklit8 Backlit Front Glossy

### PRODUCT OVERVIEW

Translucent polyester backlit film with specialized water-resistant coating

Ultra white glossy finish and durable PET base

Sharp image reproductions that stand out with the light on or off

Ideal for backlit film applications and compatible with both dye & UV pigmented based aqueous inks

### PRODUCT SUGGESTED APPLICATION

Light box advertising (graphic in the panel)

Illuminated displays

Backlit tradeshow and exhibition

Signage/banner

Department store display

### PRODUCT SPECIFICATIONS

Caliper:	215 microns (8.6 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	285g	Width:	36" / 42" / 50" / 60"
Base material:	Polyester film	Length:	30m (100 ft)
Surface:	High Glossy	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmsc.com](http://www.ddpmsc.com)