

AMMBacklit8 Backlit Front Matte 215

PRODUCT OVERVIEW

Translucent polyester backlit film with specialized water-resistant coating
Ultra white finish with durable PET base
Sharp image reproductions with light on or off
Ideal for all backlit film applications
Compatible with both dye & UV pigmented aqueous based inks

**Certified for
HP Latex Inks**

PRODUCT SUGGESTED APPLICATION

Light box advertising

Illuminated displays

Tradeshow and exhibition graphics

Signage

All retail advertisement applications

Cosmetics

Fashion imaging

Airport and transit

PRODUCT SPECIFICATIONS

Caliper: 215 microns (8.6 mil)

Weight: 270g

Base material: PET

Surface: Matte

Inks: Aqueous (inkjet) / Dye / Latex

Width: 36" / 42" / 50" / 60"

Length: 36m (100 ft)

Core: 3"

PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

ASSISTANCE

Call us at 908-686-2200 or visit www.ddpmsc.com