

Product Specification Sheet

AMMRoll-up10 Blockout Tradeshow /Rollup PET/PP Film

PRODUCT OVERVIEW

10 mil anti curl, multi-layered PET/PP film

Non-transmissive blockout for brilliant full color prints

Tear and fade resistant that will withstand all application conditions

PRODUCT SUGGESTED APPLICATION

Indoor and outdoor banners

Posters & billboards

POS printing

Retail aisle banners

Tradeshow panels

Instruction plates

PRODUCT SPECIFICATIONS

Caliper:	250 microns (10 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	215g	Width:	36" / 50" / 60"
Base material:	PET & PP	Length:	30m (100 ft)
Surface:	Matte	Core:	3"

PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

ASSISTANCE

Call us at 800-240-9455 or visit McGrannDigital.com