

Product Specification Sheet

AMMRoll-up14 Gray Backed Tradeshow PET/PP Film

PRODUCT OVERVIEW

14 mil anti curl, multi-layered PET/PP gray backed blackout film

Non-transmissive blackout and matte coating allows for brilliant full color prints

Tear & fade resistant material that withstands all applications both indoor and outdoor

PRODUCT SUGGESTED APPLICATION

Pop-up displays

POS printing

Indoor and outdoor banners

Retail aisle banners

Tradeshow

Exhibition graphics

Instruction plates

PRODUCT SPECIFICATIONS

Caliper: 350 microns (14 mil)

Weight: 410g

Base material: PET & PP

Surface: Matte

Inks: Aqueous (inkjet) / Dye

Width: 36" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

ASSISTANCE

Call us at 908-686-2200 or visit www.ddpmsc.com