

### Product Specification Sheet

## SMGClearFilm6 Clear Polyester Film Glossy

### PRODUCT OVERVIEW

5 mil eco-solvent, solvent and UV cure clear PET film  
High ink load capabilities with scratch resistant properties  
Anti curl and static treated

### PRODUCT SUGGESTED APPLICATION

Posters  
Window Display  
POS printing  
GIS / Mapping

### PRODUCT SPECIFICATIONS

Caliper:	125 microns (5 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	160g	Width:	36" / 54" / 60"
Base material:	PP	Length:	30m (100 ft)
Surface:	Glossy	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-6862200 or visit [DDPMSC.com](http://DDPMSC.com)