

Product Specification Sheet

SMMPoly8 POPUP8 8mil Smooth Rollup Banner

PRODUCT OVERVIEW

High opacity blackout film that expresses brilliant color reproduction

It has high image quality along with durability, tear-resistancy and is eco-friendly

High cost effectiveness compared to PET based rollup

Eco-friendly coating (No PVCs)

PRODUCT SUGGESTED APPLICATION

Tradeshow graphics

Rollup stands

POP/POS displays

Indoor and outdoor signage

PRODUCT SPECIFICATIONS

| | | | |
|----------------|------------------------|---------|---|
| Caliper: | 195 mic rons (7.8 mil) | Inks: | Eco-Solvent / Solvent / Latex / UV-Cure |
| Weight: | 160g | Width: | 36" / 50" |
| Base material: | Multi-layer PP | Length: | 30m (100 ft) |
| Surface: | Semi-Matte | Co re: | 3" |

PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre- and post heater settings around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

ASSISTANCE

Call us at 908-686-2200 or visit DDPMSC.com