

Product Specification Sheet

SMMRoll-up6 White PET Grey Backed Rollup Film Matte

PRODUCT OVERVIEW

6.4 mil white PET film with blockout produces photo quality high definition images
Compatible with eco-solvent / true solvent and latex inks
Will not curl, buckle, or warp
Offers a robust dimensionally stable final product

PRODUCT SUGGESTED APPLICATION

Tradeshow panels/graphics
Indoor/outdoor banners
POP/POS displays
Instruction plates
Posters
Retail aisle banners

PRODUCT SPECIFICATIONS

Caliper:	160 microns (6.4 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	220g	Width:	36" / 50" / 60"
Base material:	White PET	Length:	30m (100 ft)
Surface:	Matte	Core:	3"

PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.