

### Product Specification Sheet

## ST600 Easy-Tex Self Adhesive Wallpaper

### PRODUCT OVERVIEW

Sticks to non-porous flat surface

Removable, reusable, repositionable and removes easily with no residue

Sharp, seamless graphics and superior photographic images every time

Ideal for life size photographic cut-outs for walls and wall murals

Indoor and outdoor applications: windows, backlits, doors, sign boards, and other flat surfaces

Applies without wrinkles and does not tear

Eco-friendly coating (approved for California)

### PRODUCT SUGGESTED APPLICATION

Posters

POS/POP printing

Indoor and outdoor banners

Tradeshows panels

Exhibition graphics

Instruction plates

### PRODUCT SPECIFICATIONS

Caliper: 345 microns (13.8 mil)

Weight: 360g

Base material: 100% Polyester Woven Fabric

Surface: Matte

Inks: Eco-Solvent / Solvent / Latex / UV-Cure

Width: 24" / 36" / 54" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.